


LLC-MFT600 (LMR-600 Type)**Low Loss Flexible Coaxial Cable****Construction**

Item	Material	Diameter (inch)	Diameter (mm)
Center Conductor	Solid Copper Clad Aluminum Wire	0.1760 inch	4.47 mm
Dielectric	Foamed Polyethylene	0.455 inch	11.56 mm
Inner Shield	Sealed APA Tape	0.463 inch	11.76 mm
Outer Shield	34AWG, 90% Tinned Copper Braid	0.491 inch	12.47 mm
Jacket	Black PE	0.590 inch	14.99 mm

Electrical & Mechanical Data

Operation Frequency	30 ~ 6000 MHz
Characteristic Impedance	50 Ω
Velocity of Propagation, Nom.	86 %
Capacitance, Nom.	23.3 nF/kft (76.6 nF/km)
Inner Conductor Resistance @ 20 °C	0.6 Ω/kft (3 Ω/km)
Outer Conductor Resistance @ 20 °C	1.2 Ω/kft (4 Ω/km)

Attenuation @ 20 °C

Frequency	dB/100ft	dB/100m	Avg. Power Rating (Kw)
30 MHz	0.43	1.40	5.51
50 MHz	0.55	1.80	4.24
150 MHz	0.98	3.20	2.41
220 MHz	1.19	3.90	1.97
450 MHz	1.71	5.60	1.35
900 MHz	2.50	8.20	0.93
1500 MHz	3.32	10.90	0.70
1800 MHz	3.69	12.10	0.63
2000 MHz	3.90	12.80	0.59
2500 MHz	4.42	14.50	0.52
5800 MHz	7.25	23.80	0.32